



MAXIMA

High type of protection. Housing with convex light outlet and clear pane. Additional light outlet downwards for all versions. 1- or 2-sided escape route indication through self-adhesive escape sign foils.

Versions for surface wall and ceiling mounting and bracket and with additional accessories for pendulum and chain/wire

MOUNTING TYPES



MOUNTING TYPES WITH ACCESSORIES



TECHNICAL DATA

Housing: Polycarbonate, grey (RAL 7035)
Polyester, grey (RAL 7035)
Pane: Polycarbonate, transparent
Foil: PVC, printed
Service life $L_{80B_{20}}$: 50.000 h

Color stability: 3 SDCM
Color temperature: 4.000 K
Color rendering index: 70
Optic interface: LIFE, LIFE ECO



Commissioning: For Autotest, operating duration, operating mode PS, monitoring group and test duration are only programmable per app B.connect over smartphone locally on luminaire.

SELF-CONTAINED SUPPLY







Mains supply: 198 V – 254 V/50 Hz
Switching: Maintained and non-maintained
Ambient temperature: LIFE: -10 °C to +45 °C
LIFE ECO: 0 °C to +40 °C
Protection class: II

DECENTRAL SUPPLY

Mains supply: 24 V +/- 20 % DC
Battery supply: 24 V +/- 20 % DC
Ambient temperature: -20 °C to +40 °C
Protection class: III






CENTRAL SUPPLY

Mains supply: 198 V – 254 V/50 Hz
Battery supply: 176 V – 276 V
Ambient temperature: -20 °C to +40 °C
Protection class: II
Mains supply (alt.): 90 V – 254 V / 50/60 Hz
Battery supply (alt.): 90 V – 276 V








LIFE SELF-CONTAINED SUPPLY

10 YEARS GUARANTEE




Autotest / CableCom Order code	Logica Order code	Logica FM Order code					
Surface wall mounting (1-sided escape route indication)							
37054	37055	37056	32 m	2	1 h / 3 h / 8 h	LIFE 6.4 V / 1.5 Ah	8 VA
Surface ceiling mounting and bracket (2-sided escape route indication) ¹							
37057	37058	37059	32 m	2	1 h / 3 h / 8 h	LIFE 6.4 V / 1.5 Ah	8 VA

LIFE ECO SELF-CONTAINED SUPPLY

5 YEARS GUARANTEE



Autotest / CableCom Order code	Logica Order code	Logica FM Order code					
Surface wall mounting (1-sided escape route indication)							
36054	36055	36056	32 m	2	1 h / 3 h / 8 h	LIFE 6.4 V / 1.5 Ah	8 VA
Surface ceiling mounting and bracket (2-sided escape route indication) ¹							
36057	36058	36059	32 m	2	1 h / 3 h / 8 h	LIFE 6.4 V / 1.5 Ah	8 VA

SICURO^{LED} DECENTRAL SUPPLY





Sicuro24 Order code			
Surface wall mounting (1-sided escape route indication)			
32018	32 m	2	2.9 W
Surface ceiling mounting and bracket (2-sided escape route indication) ¹			
32019	32 m	2	2.9 W



¹ Please order additional required accessories for pendulum and chain/wire separately.



Included in scope of delivery	
Order code	Description
29001	Set of escape sign foils 
F95506	Bracket 

SICURO^{LED} CENTRAL SUPPLY

Sicuro230 Order code				
Surface wall mounting (1-sided escape route indication)				
31018	32 m	2	7.4 VA / 3.5 W	
Surface ceiling mounting and bracket (2-sided escape route indication) ¹				
31019	32 m	2	7.4 VA / 3.5 W	

Please order escape sign accessories separately	
Order code	Description
29002	Escape sign foil 
16917M	Set of escape sign foils 

Please order accessories separately	
Order code	Description
F95700	Short pendulum for ceiling mounting, incl. pendulum mounting adaptor (on-finery cable laying possible)
F95510	Tubular pendulum, round, 500 mm
F95511	Tubular pendulum, round, 1.000 mm
F95512	Tubular pendulum, round, 1.500 mm
3723	Lug set for chain and wire mounting
F95032K	Protective basket (only for surface wall mounting)