



AESTETICA

Housing in compact design with plane light outlet area and clear cover. Light guidance through plastic reflector. 1-sided escape route indication through exchangeable escape sign foils, 2-sided escape route indication through exchangeable display panes.

Versions for surface wall and ceiling mounting or with additional accessories for recessed wall mounting, recessed ceiling mounting and bracket

MOUNTING TYPES



MOUNTING TYPES WITH ACCESSORIES



TECHNICAL DATA

Housing:	Polycarbonate, white (RAL 9003)
Cover:	Polycarbonate, transparent
Display pane / pane:	PMMA, printed
Reflector:	Polycarbonate, white

Service life $L_{80B_{20}}$:	50.000 h
Color stability:	3 SDCM
Color temperature:	6.000 K
Color rendering index:	80



DECENTRAL SUPPLY

Mains supply:	24 V +/- 20 % DC
Battery supply:	24 V +/- 20 % DC
Ambient temperature:	-20 °C to +40 °C
Protection class:	III

CENTRAL SUPPLY

Mains supply:	198 V – 254 V/50 Hz
Battery supply:	176 V – 276 V
Ambient temperature:	-20 °C to +40 °C
Protection class:	II
Mains supply (alt.):	90 V – 254 V / 50/60 Hz
Battery supply (alt.):	90 V – 276 V

Variant

Sicuro24 / Sicuro230



120 lm

Sicuro24 Order code				
------------------------	---	---	---	---

Surface wall mounting (1-sided escape route indication / illumination),
surface ceiling mounting (2-sided escape route indication / illumination)¹

32069	15 m	20	120 lm	1.7 W
--------------	------	----	--------	-------









¹ Please order additional required accessories for recessed wall and ceiling mounting and bracket separately.



Sicuro230 Order code					
-------------------------	---	---	---	---	---

Surface wall mounting (1-sided escape route indication / illumination),
surface ceiling mounting (2-sided escape route indication / illumination)¹

31098	15 m	20	120 lm	4.8 VA / 1.8 W
--------------	------	----	--------	----------------



Please order escape sign accessories separately			
Order code	Description		
VD 15 m	VD 20 m		
16235	—	Escape sign pane, wall	
16236	—	Escape sign pane, wall	
16237	—	Escape sign pane, wall	
—	16233	Escape sign display pane, ceiling, bracket	
—	16234	Escape sign display pane, ceiling, bracket	

Please order accessories separately	
Order code	Description
4265	Bracket
3733	Recessed mounting set for massive walls and massive ceilings (concrete-cast housing)
4266	Recessed mounting set for hollow walls and hollow ceilings