




SIGN LED

Combined safety sign and safety luminaire. Housing made of flat sheet steel profiles with angular contours in triangular shape. 2-sided indication of safety devices through exchangeable safety sign panes. Illumination of safety devices with 5 lx through high-power LED with light guidance through special lens.

Version for surface wall mounting

MOUNTING TYPES



TECHNICAL DATA

Commissioning:

Mains supply:

Ambient temperature:

Protection class:

Switching:

Housing: Display pane:	Sheet steel, white (RAL 9003) PMMA, printed	Color temperature: 4.000 K (SSL) 6.500 K (SL)
Lens:	PMMA, transparent	Color rendering index: 70 (SSL & SL)
Service life L ₈₀ B ₂₀ :	50.000 h	Optic interface: LIFE
Color stability:	3 SDCM	► IP40 IK05

For Autotest, operating duration, operating mode PS, monitoring group and test duration are only programmable per app B.connect over smartphone locally on luminaire.

SELF-CONTAINED SUPPLY

198 V - 254 V/50 Hz

Maintained and

non-maintained

-10 °C to +45 °C

non-maintained or


DECENTRAL SUPPLY

Mains supply:	24 V +/- 20 % DC
Battery supply:	24 V +/- 20 % DC
Ambient temperature:	-20 °C to +40 °C
Protection class:	111


CENTRAL SUPPLY

Mains supply:	198 V – 254 V/50 Hz
Battery supply:	176 V – 276 V
Ambient temperature:	-20 °C to +40 °C
Protection class:	I
Mains supply (alt.):	90 V – 254 V / 50/60 Hz
Battery supply (alt.):	90 V – 276 V

Variant	Φ~
LIFE – partial component: safety luminaire	243 lm
Sicuro24 / Sicuro230 – partial component: safety luminaire	323 lm



Rev.-No. S2024-03




LIFE SELF	F-CONTAINED	SUPPLY						•	10 YEARS GUARANTEE
Autotest / CableCom Order code	Logica Order code	Logica FM Order code	☆	LED	Ф= 00 1 h	Ф= 00 3 h	Ф= 8 h	+	S~
Surface wall mounting	g (2-sided indication)	for indication and illu	mination of s	safety device	S				
37225 ¹	37226 ¹	37227 ¹	26 m	2+1	323 lm	186 lm	65 Im	2x LIFE 6.4 V / 1.5 Ah	8 VA

DECE [®]	NTRAL SU	JPPLY		
Sicuro24 Order code	✓✓✓	LED	Φ= 00	P=
Surface wall mounting (2-sided in safety devices	dication) for inc	lication and	l illumination of	of
32074 ¹	26 m	2+1	323 Im	6.7 W

[Sicuro] ** (ENTRAL	SUPPL	Y	
Sicuro230 Order code	X	LED	Φ=	S~ P=
Surface wall mounting (2-sid safety devices	led indication	n) for indicat	ion and illum	nination of
31103 ¹	26 m	2+1	323 Im	15.7 VA / 7.6 W

 $^{\scriptscriptstyle 1}$ Luminaire is equipped with 2 separate monitoring and control modules.

The operating modes of the two monitoring and control modules for illumination of the safety signs and the safety device are separately configurable.



Please order sa Order code		Description
E16914M	Ê¥	F001 safety sign pane fire extinguisher
E16915M	Ì ∭ %	F002 safety sign pane extinguishing hose
E16913M		F005 safety sign pane fire detector
E16910M	•	E003 safety sign pane first aid
E16912M	(, +	E004 safety sign pane emergency telephone
E16911M	שנ חייה	E007 safety sign pane assembly point
E16917M	÷.	E017 safety sign pane escape hatch
E16916M	4	E019 safety sign pane emergency hatch

